





# TECHNICAL DATA SHEET

NAME	REFERENCE
PUSH BUTTON OPERATED HAND DRYER IBERO SATIN STAINLESS STEEL	AA91500
DESCRIPTION	
TRADITIONAL HAND DRYER OF HIGH QUALITY AND PERFORMANCE	
DOUBLE ELECTRICAL INSULATION MANUALLY OPERATED START, AUTOMATIC STOP CLASS II: NO GROUNDING WIRE REQUIRED, PLACED 0,6 mts FROM WATER POINT HIGH QUALITY SATIN INOX	
ELECTRICAL SCHEME	 <p>1. THERMAL FUSE 2. THERMAL CUT-OFF (IN HEATING ELEMENT) 3. HEATING ELEMENT POWER 1800 W 230 V- 50 HZ 4. THERMAL CUT-OFF (IN MOTOR) 5. MOTOR 230 V - 50 HZ 6. TIMER SWITCH</p>
	EAN CODE
	8427950323072

CHARACTERISTICS				
NET (without packaging)	DIMENSIONS (mm)	HEIGHT: 220	WIDTH: 280	DEPTH: 210
	WEIGHT (Kg)	3,695		
GROSS (with packaging)	DIMENSIONS (mm)	HEIGHT: 285	WIDTH: 345	DEPTH: 295
	WEIGHT (Kg)	4,390		
MATERIALS	SATIN STAINLESS STEEL INOX AISI 304 COVER INTERNAL COMPONENTS IN ABS AND POLYCARBONATE "VO" PUSH BUTTON AND NOZZLE IN CHROME ABS			
COLOUR / FINISH	SATIN STAINLESS STEEL COVER CHROME PUSH BUTTON AND NOZZLE			
ELECTRICAL FEATURES	VOLTAGE: 230V. AC FREQUENCY: 50 Hz. CONSUMPTION: 8,8 Amp. MOTOR POWER: 200 W. HEATING ELEMENT POWER: 1800 W. TOTAL POWER: 2000 W. MOTOR RPM: 4250 TYPE OF MOTOR : BRUSHED		AIRSPEED: 121 Km/HOUR EFFECTIVE AIRFLOW: 300 m³/HOUR SOUND PRESSURE: 77,5 Db. AIR TEMPERATURE: 54,1 °C (At a distance of 10 cm) ELECTRICAL INSULATION: CLASS II CERTIFICATIONS: TÜV, GS, UL AND CE PROTECTION RATIO: IP23	
	FIXING	BY MEANS OF 4 SCREWS AND 4 WALL PLUGS - INCLUDED		
PACKAGING	SINGLE UNIT PACKAGING		Approved by : Quality Control Dept	
			DATE: 12/05/2015	